Chief, KURIOT  AQUATE / Operational  Air-Fed Incinerator  ROUNED  Home  1. Headquarters is pleased to learn that incinerators similar to the type developed by KURIOT.  2. should be unde sware that when the program was initiated for the development of an air-fed incinerator the basic use of the incinerator was to be emergency destruction. After the first unit was installed at be used for the routine destruction of its classified waste files.  3. Explaining the amount of effluent emitted is rather difficult. At no time does the effluent emission ever exceed a number 2 on the Ringlesma Smoke Chart. During operation, with the exception of the Ringlesma Smoke Chart. During operation, with the exception of the Ringlesma Chart. During burning a slight gray hase, from the clay in the paper being exhausted, appears at the end of the stack. Black flecks will appear as small pieces of fly-sels are entited. Unfortunately there isn't too much information available since only two units are presently in use. As soon as the three additional incinerators are placed in the field, more information of this type should become available.  4. Using the air-fed incinerator located in the headquarters area, two engineers were able to destroy 2,276 pounds of paper in approximately six hours. One man was able to destroy apparation at paper in approximately six hours. One man was able to destroy apparation at paper in approximately six hours. One man was able to destroy apparation at paper in approximately six hours. One man was able to destroy apparation at paper in approximately six hours. One man was able to destroy apparation at paper and apparation apparation of the structure apparation at a paper in approximately six hours. One man was able to destroy apparation at a paper and apparation apparation of the structure apparation a	Chief, HURIOT  AGUATIC Operational  Air-Fed Insinerator  Rome  1. Readquarters is pleased to learn that  The Monogenic Country  Rome  1. Readquarters is pleased to learn that  Insinerator similar to the type developed by MURIOT.  2. should be made aware that when the program was initiated for the development of an air-fed insinerator the basic use of the incinerator was to be emergency destruction. After the first unit was installed at be used for the routine destruction of its classified waste files.  3. Explaining the amount of effluent emitted is rather difficult. At no time does the effluent emission ever exceed a number 2 on the Ringleman Smobe Chart. During operation, with the exception of the time when feeding is taking place, the emission is closer to \(\frac{1}{2}\) on the Ringleman Chart. During burning a slight gray hape, from the clay in the paper being exhausted, appears at the end of the stack. Black flecks will appear as small pieces of fly-ash are emitted. Unfortunately there in to ome information available since only two units are presently in use. As soon as the three additional insinerators are placed in the field, more information available since only two units are presently in use. As soon as the three additional insinerators are placed in the field, more information of this type should become available.  4. Using the air-fed insinerator located in the headquarters area, two engineers were able to destroy 2,276 pounds of paper in approximately six hours. One man was able to destroy approximately 2,000 pounds of paper in an eight hour day. This paper was peaked in one cubic foot boxes. Most of these boxes were opened and the contents were thrown into the burning chamber. The fibreboard boxes were destroyed at the sent of the day. Burning at these rates will keep the operators relatively busy, but not overburdened.	Chief, KURIOT  AQUATE / Operational  Air-Fed Incinerator  None  1. Headquarters is pleased to learn that incinerators similar to the type developed by KURIOT.  2. should be unde aware that when the program was initiated for the development of an air-fed incinerator the basic use of the incinerator was to be emergency destruction. After the first unit was installed at be used for the routine destruction of its classified waste files.  3. Explaining the amount of effluent emitted is rather difficult. At no time does the effluent emission ever exceed a number 2 on the Ringleman Smoke Chart. During operation, with the exception of the time when feeding is taking place, the emission is closer to \(\frac{1}{2}\) on the Ringleman Chart. During burning a slight gray hase, from the clay in the paper being exhausted, appears at the end of the stack. Black flocks will appear as small pieces of fly-seh are emitted. Unfortunately there isn't too much information available since only two units are presently in use. As soon as the three additional incinerators are placed in the field, more information available since only two units are presently in use. As soon as the three additional incinerators are placed in the field, more information in closeted in the headquarters area, two engineers were able to destroy 2,276 pounds of paper in approximately six hours. One man was able to destroy approximately 2,000 pounds of paper in an eight hour day. This paper was packed in one cubic foot boxes. Most of these boxes were opened and the contents were thrown into the burning chamber. The fibreboard boxes were destroyed at the end of the day. Burning at these reties will here the operators relatively	Chief, HIRIOT  AART For Incinerator  Chief, HIRIOT  AART For Incinerator  AART For Incinerator  Incinerator is pleased to learn that  Incinerator is should be under source that when the program was initiated for the development of an air-fed incinerator the basic use of the incinerator was to be emergency destruction. After the first unit was installed at destruction of offluent entitled is retained that incinerator would be used for the routine destruction of offluent entitled is retained infinitely.  At no time does the effluent entesion ever caused a number 2 on the Ringleson Schole Cheart. Buring spreasion, provided the sucception of the time when feeding is taking place, the entesions at the conception of the Ringleson Chert. Buring pursue, a slight gray hear, from the paper as small pieces of fly-sole are entited. Informaticly there isn't too much information available since only two units are presently in use. As soon as the three additional incinerators are placed in the field, more information of this type should become available.  A. Using the air-fed incinerator located in the headquarters area, two engineers were subtle to destroy 2,7% pounds of paper in an eight hour day. This paper was pasked in one cubic foot boxes. Most of these boxes were spend and the contents were thrown into the burning chamber. The fibrohord boxes were destroyed at the end of the day. Enring at those reases will keep the operators relatively busy, but not ever-blower constinctions (electrical motor-blower and agasoline engine-blower). The electrical motor and blower unit is equipped to the air inlet duet provided. The motor of the contents were charged at the end of the day. Enring at these reases will keep the operators relatively busy but not ever-blower constinctions (electrical motor-blower and and examples and consecution one and enumerating consecution to the available	DISPATCH	CLASSIFICATION	DISPATCH SYMBOL AND NO.		
Chief, KURIOT  AQUATE / Operational  AT-Fed Incinerator  REDUCED  Home  1. Readquarters is pleased to learn that incinerators similar to the type developed by KURIOT.  2. should be made aware that when the program was initiated for the development of an air-fed incinerator was to be emergency destruction. After the first unit was installed at decided this incinerator would be used for the routine destruction of its classified waste files.  3. Explaining the amount of effluent emitted is rather difficult. At no time does the effluent emission ever exceed a number 2 on the Ringlessan Smoke Chart. During operation, with the exception of the time when feeding is taking place, the emission is closer to 2 on the Ringlessan Chart. Buring burning a slight gray hase, from the clay in the paper being exhausted, appears at the end of the stack. Black flecks will appear as small pieces of fly-sch are entited. Unfortunately there isn't too much information available since only two units are presently in use. As soon as the three additional incinerators are placed in the field, more information of this type should become available.  4. Using the air-fed incinerator located in the headquarters area, two engineers were able to destroy 2,276 pounds of paper in approximately six hours. One man was able to destroy apparation and the paper in approximately six hours. One man was able to destroy apparation of the paper in approximately six hours. One man was able to destroy apparationately 2.000 pounds of paper in approximately six hours. One man was able to destroy apparationation 2.000 paper in approximately six hours. One man was able to destroy apparationative 2.000 papers and the stack and the stack area.	Chief, KURIOT  AQUATIC / Operational  Air-Fed Incinerator  1. Headquarters is pleased to learn that incinerators similar to the type developed by KURIOT.  2. should be used sware that when the program was initiated for the development of an air-fed incinerator the basic use of the incinerator was to be emergency destruction. After the first unit was installed at decided this incinerator would be used for the routine destruction of its classified waste files.  3. Explaining the amount of effluent emitted is rather difficult. At no time does the effluent emission ever exceed a number 2 on the Ringleman Smoke Chart. During operation, with the exception of the time when feeding is taking place, the emission is closer to \(\frac{1}{2}\) on the Ringleman Chart. During burning a slight gray hase, from the clay in the paper being exhausted, appears at the end of the stack. Black flocks will appear as small places of fly-ash are emitted. Unfortunately there isn't too much information available since only two units are presently in use. As soon as the three additional incinerators are placed in the field, more information of this type should become available.  4. Using the air-fed incinerator located in the headquarters area, two engineers were able to destroy 2,276 pounds of paper in approximately six hours. One man was able to destroy spproximately 2,000 pounds of paper in an eight hour day. This paper was packed in one cubic foot boxes. Most of these boxes were opened and the contexts were thrown into the burning chamber. The fibreboard boxes were destroyed at the end of the day. Burning at these rates will keep the operators relatively busy, but not overburdened.	Chief, KURIOT  AQUATE /Operational  Air-Fed Insinerator  Rome  1. Headquarters is pleased to learn that  Include the second of t	Chief, KURHOT  AQUATIC / Operational  Alt. Fed Insinerator  Brown  1. Readquarters is pleased to learn that  Insinerators similar to the type developed by KURHOT.  2. should be unde source that shen the program was initiated for the development of an air-fed insinerator the basic use of the insinerators similar to the type developed by KURHOT.  2. should be unde source that shen the program was initiated for the development of an air-fed insinerator the basic use of the insinerator was the sentence of the insinerator would be used for the routine destruction of its elementary are used instance of the insinerator would be used for the routine destruction of its elementary of the Ringlesan Sanks Chart. During operation, with the exception of the Ringlesan Sanks Chart. During operation, with the exception of the Ringlesan Sanks Chart. During operation, with the exception of the Ringlesan Sanks Chart. During operation, with the exception of the Ringlesan Sanks Insinerator would be used for the routine of the stake. Black flacks will appear as small pieces of fly-sels are emitted. Unfortunately there isn't too mak information of this type should become available.  4. Using the air-fed insinerator located in the headquarters are, two engineers were able to destroy 2,765 pounds of paper in approximately as in hourse. One san was able to destroy operationally 2,000 pounds of paper in an eight hour day. This paper was packed in one cubic foot boxes. Should the sense available.  5. The instance the boxes were operated and the entitles were thrown into the flack, sure information of this type should become available.  5. The instance the boxes were operated and the entitles of the sind of the sanks of the stake of the sanks of t	DISPAICH	SECRET		2	
Chief, KURIOT  AQUATE/Operational  Air-Fed Insinerator  ROURD  Bone  1. Headquarters is pleased to learn that insinerators similar to the type developed by KURIOT.  2. should be made aware that when the program was initiated for the development of an air-fed insinerator the basic use of the insinerator was to be emergency destruction. After the first unit was installed at decided this insinerator would be used for the routine destruction of its classified waste files.  3. Explaining the amount of effluent existed waste files.  At no time does the effluent existing place, the existing is closer to 2 on the Ringlesan Chart. During operation, with the exception of the time when feeding is taking place, the existing is closer to 2 on the Ringlesan Chart. During burning a slight gray hase, from the clay in the paper being exhausted, appears at the end of the stack. Black flecks will appear as small pieces of fly-sen are emitted. Unfortunately there isn't too much information available since only two units are presently in use. As soon as the three additional incinerators are placed in the field, more information of this type should become available.  4. Using the air-fed incinerator located in the headquarters area, two engineers were able to destroy 2,276 pounds of paper in approximately slowers.	Chief, KURIOT  AQUATIE/Operational  Air-Fed Insinerator  1. Readquarters is pleased to learn that  Incinerator similar to the type developed by KURIOT.  2. Should be made aware that when the program was initiated for the development of an air-fed incinerator the basic use of the incinerator was to be emergency destruction. After the first unit was installed at decided this incinerator would be used for the routine destruction of its classified wast files.  3. Explaining the amount of effluent exitted is rather difficult. At no time does the effluent emission ever exceed a number 2 on the Ringleman Smoke Chart. During operation, with the exception of the time when feeding is taking place, the emission is elever to \$\frac{1}{2}\$ on the Ringleman Chart. During burning a slight gray hase, from the clay in the paper being exhausted, appears at the end of the stack. Black flacks will appear as small pieces of fly-ash are emitted. Unfortunately there isn't too much information available since only two units are presently in use. As soon as the three additional incinerators are placed in the field, more information of this type should become available.  4. Using the air-fed incinerator located in the headquarters area, two engineers were able to destroy approximately 2,000 pounds of paper in an eight hour day. This paper was packed in one cubic foot boxes. Most of these boxes were opened and the contents were thrown into the burning chamber. The fibreboard boxes were destroyed at the end of the day. Burning at these rates will keep the operators relatively busy, but not overburdened.	Chief, KURIOT  AQUATE / Operational.  Air-Fed Incinerator  Rouse  1. Headquarters is pleased to learn that may have use for incinerators similar to the type developed by HURIOT.  2. should be made aware that when the program was initiated for the development of an air-fed incinerator the basic use of the incinerator was to be emergency destruction. After the first unit was installed at be used for the routine destruction of its classified waste files.  3. Explaining the amount of effluent exited is rather difficult. At no time does the effluent existion ever emesed a number 2 on the Ringleson Smoke Chart. During operation, with the exception of the time when feeding is taking place, the existion is closer to \( \frac{1}{2} \) on the Ringleson Smoke Chart. During operation, with the exception of the time when feeding is taking place, the existion is closer to \( \frac{1}{2} \) on the Ringleson Smoke Chart. During operation, with the exception of the time when feeding is taking place, the existion is closer to \( \frac{1}{2} \) on the Ringleson Smoke Chart. During operation, with the exception of the time when feeding is taking place, the existion is closer to \( \frac{1}{2} \) on the Ringleson Smoke Chart. During operation, with the exception of the time when feeding is taking place, the existion when the last riches really there is at the mesh information available since only two units are presently there is at the mesh information available since only two units are presently in use. As soon as the three additional incinerators are placed in the field, some information of this type should become available.  4. Using the air-fed insinerator located in the headquarters area, two engineers were able to destroy 2,276 pounds of paper in an eight hour day. This paper was packed in one cubic foot boxes. Not of these boxes were opened and the contents were thrown into the burning chamber. The fibreboard boxes were destroyed at the and of the day. Burning at these rates will keep the operators relatively busy, but not o	Chief, MUNIOF  AQUATE/Operational  Attr-Fed Insinerator  None  1. Headquarters is pleased to learn that  insinerators shallar to the type developed by MINIOF.  2. should be used sware that when the program was initiated for the development of an atr-fed insinerator the basic use of the incinerator was to be seargency destruction. After the first unit was installed at be used for the routine destruction after the first unit was installed at be used for the routine destruction after the first unit was installed at be used for the routine destruction after the first unit was installed at be used for the routine destruction of the classified waste files.  3. Explaining the amount of effluent entated is rather difficult. At no time does the effluent entasion ever exceed a number 2 on the Ringleam Shoke Chart. During operation, with the exception of the time when feeding is taking place, the entasion is closer to 2 on the Ringleam Shoke Chart. During operation, with the enception of the purple being exhausted, appears at the end of the stock. Black flacks will appear as small pleases of fly-sals are entited. Unfortunately there isn't too much information available since only two units are presently in use. As soon as the three additional incinerators are placed in the field, sore information of this type should become available.  4. Using the air-fed incinerator located in the headquarters area, two engineers were able to destroy 2,276 pounds of paper in approximately six hours. One man was able to destroy approximately 2,000 pounds of paper in an eight hour day. This paper was peaked in one cubic foot boxes. Nost of these boxes were opened and the contents were thrown into the bluming chamber. The fitherboard boxes were destroyed at the end of the day. Europe and the contents were thrown into the bluming chamber. The fitherboard boxes were destroyed at the end of the day. Europe and the contents were thrown into the string chamber. The fitherboard boxes are destroyed at the end of the air interval. Should the exerci			HEADQUARTERS FILE NO.		
Chief, KURIOT  AGUATIC/Operational  Air-Fed Incinerator  ROUNDER  Bone  1. Headquarters is pleased to learn that incinerators similar to the type developed by HURIOT.  2. should be made sware that when the program was initiated for the development of an air-fed incinerator the basic use of the incinerator was to be emergency destruction. After the first unit was installed at decided this incinerator would be used for the routine destruction of its classified waste files.  3. Explaining the amount of effluent emitted is rather difficult. At no time does the effluent emission ever emeed a number 2 on the Ringleman Smoke Chart. During operation, with the exception of the Ringleman Chart. During burning a slight gray hase, from the clay in the paper being exhausted, appears at the end of the stack. Black flecks will appear as small pieces of fly-esh are emitted. Unfortunately there isn't too much information available since only two units are presently in use. As soon as the three additional incinerators are placed in the field, more information of this type should become available.  4. Using the air-fed incinerator located in the headquarters area, two engineers were able to destroy 2,276 pounds of paper in approximately six hours. One man was able to destroy approximately 2,000 pounds of	AQUATIC Operational  Air-Fed Incinerator  No INDEXING CAN SE JUDGED  NOT INCINED TO SET INDEXING  AIR FED FOR INDEXING  TX NO INDEXING REQUIRED  NOT INDEXING CAN SE JUDGED  NOT INCINED TO SET INDEXING  AIR FED FOR INDEXING  TX NO INDEXING REQUIRED  NOT INDEXING CAN SE JUDGED  NOT INDEXING REQUIRED  NOT INDEXING CAN SE JUDGED  A SET JUDGED  NOT INDEXING  A SET JUDGED  A SET JUDGED  NOT INDEXING  A SET JUDGED  A SET JUDGED  NOT INDEXING  A SET JUDGED  A SET JUDGE  A SET JUDGED  A SET JUDGE  A SET JUDGED  A SET JUDGE	AGUATIC /Operational  AIT-Fed Incinerator  AQUATIC /Operational  AIT-Fed Incinerator  RODED  1. Headquarters is pleased to learn that  Incinerators similar to the type developed by HURIOT.  2. should be made aware that when the program was initiated for the development of an air-fed incinerator the basic use of the incinerator was to be emergency destruction. After the first unit was installed at decided this incinerator would be used for the routine destruction of its classified waste files.  3. Explaining the amount of effluent emitted is rather difficult. At no time does the effluent emission ever exceed a number 2 on the Ringleman Smoke Chart. During operation, with the exception of the time when freeding is taking place, the emission is closer to \$\frac{1}{2}\$ on the Ringleman Chart. During burning a slight gray hase, from the clay in the paper being exhausted, appears at the end of the stack. Black flecks will appear as small places of fly-each are emitted. Unfortunately there isn't to mech information available since only twe units are presently in use. As soon as the three additional incinerators are placed in the field, more information of this type should become available.  4. Using the air-fed incinerator located in the headquarters area, two engineers were able to destroy approximately \$2,000 pounds of paper in an eight hour day. This paper was peaked in one cubic foot boxes. Nost of these boxes were opened and the contents were thrown into the burning chamber. The fibreboard boxes were destroyed at the end of the day. Burning at these rates will keep the operators relatively busy, but not overburdened.  5. The incinerator presently located at with two motor-blower and generator in the building will come on and provide the mecessary current. Rowers, in the building will come on and provide the mecessary current. Rowers in the building will come on and provide the mecessary current. Rowers in the building will come on and provide the mecessary current. Rowers in the building will come on and provide	Chief, NURIOT  All-Fed Insinerator  In MARKE For MORNES  All-Fed Insinerator  In MARKE FOR MORNES  All-Fed Insinerator  In MARKE FOR MORNES  AND MORNES COLUMN  MORNES COLU			REF: AQUATIC		
Chief, KURIOT  AGUATIC/Operational  Air-Fed Incinerator  ROUNDER  Bone  1. Headquarters is pleased to learn that incinerators similar to the type developed by HURIOT.  2. should be made sware that when the program was initiated for the development of an air-fed incinerator the basic use of the incinerator was to be emergency destruction. After the first unit was installed at decided this incinerator would be used for the routine destruction of its classified waste files.  3. Explaining the amount of effluent emitted is rather difficult. At no time does the effluent emission ever emeed a number 2 on the Ringleman Smoke Chart. During operation, with the exception of the Ringleman Chart. During burning a slight gray hase, from the clay in the paper being exhausted, appears at the end of the stack. Black flecks will appear as small pieces of fly-esh are emitted. Unfortunately there isn't too much information available since only two units are presently in use. As soon as the three additional incinerators are placed in the field, more information of this type should become available.  4. Using the air-fed incinerator located in the headquarters area, two engineers were able to destroy 2,276 pounds of paper in approximately six hours. One man was able to destroy approximately 2,000 pounds of	AQUATIC Operational  Air-Fed Incinerator  No INDEXING CAN SE JUDGED  NOT INCINED TO SET INDEXING  AIR FED FOR INDEXING  TX NO INDEXING REQUIRED  NOT INDEXING CAN SE JUDGED  NOT INCINED TO SET INDEXING  AIR FED FOR INDEXING  TX NO INDEXING REQUIRED  NOT INDEXING CAN SE JUDGED  NOT INDEXING REQUIRED  NOT INDEXING CAN SE JUDGED  A SET JUDGED  NOT INDEXING  A SET JUDGED  A SET JUDGED  NOT INDEXING  A SET JUDGED  A SET JUDGED  NOT INDEXING  A SET JUDGED  A SET JUDGE  A SET JUDGED  A SET JUDGE  A SET JUDGED  A SET JUDGE	AGUATIC /Operational  AIT-Fed Incinerator  AQUATIC /Operational  AIT-Fed Incinerator  RODED  1. Headquarters is pleased to learn that  Incinerators similar to the type developed by HURIOT.  2. should be made aware that when the program was initiated for the development of an air-fed incinerator the basic use of the incinerator was to be emergency destruction. After the first unit was installed at decided this incinerator would be used for the routine destruction of its classified waste files.  3. Explaining the amount of effluent emitted is rather difficult. At no time does the effluent emission ever exceed a number 2 on the Ringleman Smoke Chart. During operation, with the exception of the time when freeding is taking place, the emission is closer to \$\frac{1}{2}\$ on the Ringleman Chart. During burning a slight gray hase, from the clay in the paper being exhausted, appears at the end of the stack. Black flecks will appear as small places of fly-each are emitted. Unfortunately there isn't to mech information available since only twe units are presently in use. As soon as the three additional incinerators are placed in the field, more information of this type should become available.  4. Using the air-fed incinerator located in the headquarters area, two engineers were able to destroy approximately \$2,000 pounds of paper in an eight hour day. This paper was peaked in one cubic foot boxes. Nost of these boxes were opened and the contents were thrown into the burning chamber. The fibreboard boxes were destroyed at the end of the day. Burning at these rates will keep the operators relatively busy, but not overburdened.  5. The incinerator presently located at with two motor-blower and generator in the building will come on and provide the mecessary current. Rowers, in the building will come on and provide the mecessary current. Rowers in the building will come on and provide the mecessary current. Rowers in the building will come on and provide the mecessary current. Rowers in the building will come on and provide	Chief, NURIOT  All-Fed Insinerator  In MARKE For MORNES  All-Fed Insinerator  In MARKE FOR MORNES  All-Fed Insinerator  In MARKE FOR MORNES  AND MORNES COLUMN  MORNES COLU					
Chief, KURIOT  AQUATE / Operational  Air-Fed Incinerator  REQUIRED  Home  1. Headquarters is pleased to learn that  incinerators similar to the type developed by KURIOT.  2. should be used sware that when the program was initiated for the developeant of an air-fed incinerator the basic use of the incinerator was to be emergency destruction. After the first unit was installed at decided this incinerator would be used for the routine destruction of its classified waste files.  3. Explaining the amount of effluent emitted is rather difficult. At no time does the effluent emission ever exceed a number 2 on the Ringleman Smoke Chart. During operation, with the exception of the Ringleman Chart. During operation, with the exception of the Ringleman Chart. During burning a slight gray hase, from the clay in the paper being exhausted, appears at the end of the stack. Black fleeks will appear as small pieces of fly-each are emitted. Unfortunately there isn't too much information available since only two units are presently in use. As soon as the three additional incinerators are placed in the field, more information of this type should become available.  4. Using the air-fed incinerator located in the headquarters area, two engineers were able to destroy asmortantally 2.000 pounds of	Air-Fed Incinerator  Air-Fed Incinerator  1. Headquarters is pleased to learn that  incinerators similar to the type developed by EURIOT.  2. should be used sware that when the program was initiated for the development of an air-fed incinerator the basic use of the incinerator was to be emergency destruction. After the first unit was installed at decided this incinerator would be used for the routine destruction of its classified waste files.  3. Explaining the amount of effluent emitted is rather difficult. At no time does the effluent emission ever emeed a number 2 on the Ringleman Smoke Chart. During operation, with the exception of the time when feeding is taking place, the emission is closer to 2 on the Ringleman Chart. During burning a slight gray hase, from the clay in the paper being exhausted, appears at the end of the stack. Black flecks will appear as small pieces of fly-ash are emitted. Unfortunately there isn't too much information of this type should become available.  4. Using the air-fed incinerator located in the headquarters area, two engineers were able to destroy 2.276 pounds of paper in approximately six hours. One man was able to destroy 2.276 pounds of paper in approximately six hours. One man was able to destroy approximately 2.000 pounds of paper in an eight hour day. This paper was packed in one cubic foot boxes. Most of these boxes were opened and the contents were thrown into the burning chamber. The fibreboard boxes were destroyed at the end of the day. Burning at these rates will beep the operators relatively busy, but not overburdened.	Air-Fed Insinerator  Air-Fed Insinerator  Air-Fed Insinerator  Rouse  1. Headquarters is pleased to learn that    MARKED FOR ROBERDS   MONDRING ROUNDED	AGENTE/Operational Ar-Fed Incinerator  Home  1. Headquarters is pleased to learn that  IN NO NORMO SCALED  MONORMO SCALED  MON			DATE		
AGUNTE / Operational  Air-Fed Incinerator  Rome  1. Headquarters is pleased to learn that incinerators similar to the type developed by HURIOT.  2. should be made sware that when the program was initiated for the development of an air-fed incinerator the basic use of the in- cinerator was to be emergency destruction. After the first unit was installed at be used for the routine destruction of its classified waste files.  3. Explaining the amount of effluent emitted is rather difficult. At no time does the effluent emission ever emeed a number 2 on the Ringleman Smoke Chart. During operation, with the exception of the time when feeding is taking place, the emission is closer to \( \frac{1}{2} \) on the Ringleman Chart. During burning a slight gray hase, from the clay in the paper being emisuated, appears at the end of the stack. Black flecks will appear as small pieces of fly-ash are emitted. Black flecks will appear as small pieces of fly-ash are emitted. Black flecks will appear as small pieces of fly-ash are emitted. Black flecks will appear as small pieces of fly-ash are emitted. Black flecks will appear as small pieces of fly-ash are emitted. Black flecks will appear as small pieces of fly-ash are emitted. Black flecks will appear as small pieces of fly-ash are emitted. Black flecks will appear as small pieces of fly-ash are emitted. Black flecks will appear as small pieces of fly-ash are emitted. Black flecks will appear as small pieces of fly-ash are emitted. Black flecks will appear as small pieces of fly-ash are emitted. Black flecks will appear as small pieces of fly-ash are emitted. Black flecks will appear as small pieces of fly-ash are emitted. Black flecks will appear as small pieces of fly-ash are emitted. Black flecks will appear as small pieces of fly-ash are emitted. Black flecks will appear as small pieces of fly-ash are emitted. Black flecks will appear as small pieces of fly-ash are emitted. Black flecks will appear as small pieces of fly-ash are emitted. Black flecks will appear as small pi	Air-Fed Incinerator  1. Hesdquarters is pleased to learn that  No Nober Score  1. Hesdquarters is pleased to learn that  Incinerators similar to the type developed by KURIOT.  2. should be used aware that when the program was initiated for the development of an air-fed incinerator the basic use of the incinerator was to be emergency destruction. After the first unit was installed at decided this incinerator would be used for the routine destruction of its classified waste files.  3. Explaining the amount of effluent emitted is rather difficult. At no time does the effluent emission ever exceed a number 2 on the Ringleman Smoke Chart. During operation, with the exception of the Ringleman Smoke Chart. During operation, with the exception of the Ringleman Chart. During burning a slight gray hase, from the clay in the paper being exhausted, appears at the end of the stack. Black fleeks will appear as small pieces of fly-ash are emitted. Unfortunately there isn't too much information available since only two units are presently in use. As soon as the three additional incinerators are placed in the field, more information of this type should become available.  4. Using the sir-fed incinerator located in the headquarters area, two engineers were able to destroy 2,276 pounds of paper in approximately six hours. One san was able to destroy approximately 2,000 pounds of paper in an eight hour day. This paper was packed in one cubic foot boxes. Most of these boxes were opened and the contents were thrown into the burning chamber. The fibreboard boxes were destroyed at the end of the day. Burning at these rates will keep the operators relatively busy, but not everburdened.	Air-Fed Incinerator  Air-Fed Incinerator  Rouse  1. Headquarters is pleased to learn that incinerators similar to the type developed by KURIOT.  2. should be used source that when the program was initiated for the development of an air-fed incinerator the basic use of the in- cinerator was to be emergency destruction. After the first unit was installed at be used for the routine destruction of its classified waste files.  3. Explaining the amount of effluent exitted is rather difficult. At no time does the effluent emission ever emseed a number 2 on the Ringlessan Smoke Chart. During operation, with the exception of the time when feeding is taking place, the emission is closer to 2 on the Ringlessan Chart. During place, the emission is closer to 2 on the Ringlessan Chart. During place, the emission is closer to 2 on the Ringlessan Chart. During a slight gray hame, from the clay in the paper being exhausted, appears at the end of the stock. Black flecks will appear as small pieces of fly-ash are emitted. Unfortunately there isn't too much information available since only two units are presently in use. As soon as the three additional incinerators are placed in the field, more information of this type should become available.  4. Using the air-fed incinerator located in the headquarters area, two engineers were able to destroy 2,276 pounds of paper in approximately six hours. One was was able to destroy approximately 2,000 pounds of paper in an eight hour day. This paper was packed in one cubic foot boxes. Most of these boxes were opened and the contents were throw into the burning chamber. The fibreboard boxes were destroyed at the end of the day. Burning at these rates will keep the operators relatively busy, but not overburdened.  5. The incinerator presently located at with two motor-blower combinations (electrical motor-blower and gasoline engine-blower). The electrical motor and blower unit is commented to the air inlat dust provided. The motor, in this case, runs off the available sity current. Should the	All-Yed Insinerator  All-Yed Insinerator  An-Yed Insinerator  No morned formation  Rome  1. Headquarters is pleased to learn that  incinerators similar to the type developed by HURIOT.  2. should be unde assure that when the program was initiated for the development of an air-fed incinerator to besid use of the incinerator was to be emergency destruction. After the first unit was installed at decided this insinerator would be used for the routine destruction of its classified waste files.  3. Explaining the assount of effluent exitted is rather difficult. At no time does the effluent existion ever exceed a number 2 on the Ringleson Sauke Chart. During operation, with the exception of the time when feeding is taking place, the existion is closer to \$ on the Ringleson Sauke Chart. During operation, with the exception of the time when feeding is taking place, the existion is closer to \$ on the Ringleson Sauke Chart. During operation, with the exception of the time when feeding is taking place, the existion is closer to \$ on the Ringleson Sauke Chart. During operation, with the exception of the time paper being exhausted, appears at the end of the stack. Risek flecks will appear as small pieces of fly-sack are emitted. Unfortunately there isn't too much information available since only the units are presently in use. As soon as the three additional instructors are placed in the field, more information of this type should become available.  4. Using the air-fed incinerator leasted in the handquarters area, two engineers were suble to destroy 2,270 pounds of paper in an eight hour day. This paper was peaked in one online from the burning chasses. The fibraboard bosons were destroyed at the end of the day. Burning at these traces will beep the operators relatively bury, but not overdurdened.  5. The incinerator presently located at with two motor-blower conditations (electrical motor and blower unit is string adjacent to the air lake dury towards. Browless and can be utilized by disconnecting one and acconnecting the	Chief, KURIOT				
Air-Fed Incinerator    XX   NO INDEXING REQUIRED	Air-Fed Incinerator  No Mexico Required  No Me	ROUND  Air-Fed Incidentator  No North Education  Not North Education  North	None  1. Headquarters is pleased to learn that incinerators similar to the type developed by NURIOT.  2. should be made source that then the program was initiated for the developent of an air-feed incinerator the basic use of the incinerators was to be emergency destruction. After the first unit was installed at developent of an air-feed incinerator was to be emergency destruction. After the first unit was installed at the used for the routine destruction of its classified waste files.  3. Explaining the amount of effluent emitted is rather difficult. At no time does the effluent emission ever exceed a number 2 on the Ringlessan Guake Chart. During operation, with the exception of the time when feeding is taking place, the emission is closer to 3 on the Ringlessan Chart. During operation, with the exception of the time when feeding is taking place, the emission is closer to 3 on the Ringlessan Chart. During a slight gray hase, from the clay in the paper being emissisted, appears at the end of the stack. Black fleeks will appear as small pieces of fly-each are emitted. Unfortunately there isn't too much information available since only two units are presently in use. As soon as the three additional indiscrutors are placed in the field, more information available since only two units are presently in use. As soon as the three additional indiscrutors are placed in the field, more information of this type should become available.  4. Using the air-fed insinerator located in the headquarters are, two engineers were able to destroy 2,276 pounds of paper in approximately six hours. One sam was able to destroy approximately 2,000 pounds of paper in an eight hour day. This paper was packed in one cubic foot boxes. Nost of these boxes were opened and the contents were thrown into the burning chamber. The fibreboard boxes were detroyed at the end of the day. Burning at these rates will keep the operators relatively busy, but not overturdend.  5. The insinerator presently located at the entents were to generator my office		.1	RE: "43-3" — (CHECK "X" ONE)		
Rome  1. Headquarters is pleased to learn that may have use for incinerators similar to the type developed by MURIOT.  2. should be made soure that when the program was initiated for the development of an air-fed incinerator the basic use of the incinerator was to be emergency destruction. After the first unit was installed at decided this incinerator would be used for the routine destruction of its classified waste files.  3. Explaining the amount of effluent emitted is rather difficult. At no time does the effluent emission ever exceed a number 2 on the Ringleman Smoke Chart. During operation, with the exception of the time when feeding is taking place, the emission is closer to ½ on the Ringleman Chart. During bluming a slight gray hase, from the clay in the paper being exhausted, appears at the end of the stack. Black flecks will appear as small pieces of fly-ash are emitted. Unfortunately there isn't too much information available since only two units are presently in use. As soon as the three additional incinerators are placed in the field, more information of this type should become available.  4. Using the air-fed incinerator located in the headquarters area, two engineers were able to destroy 2,276 pounds of paper in approximately six hours. One man was able to destroy approximately 2.000 nounds of	Home  1. Headquarters is pleased to learn that incinerators similar to the type developed by KURIOT.  2. should be unde aware that when the program was initiated for the development of an air-fed incinerator the basic use of the incinerator was to be emergency destruction. After the first unit was installed at decided this incinerator would be used for the routine destruction of its classified waste files.  3. Explaining the amount of effluent emitted is rather difficult. At no time does the effluent emission ever exceed a number 2 on the Ringleman Smoke Chart. During operation, with the exception of the time when feeding is taking place, the emission is closer to \$\frac{1}{2}\$ on the Ringleman Chart. During burning a slight gray hase, from the clay in the paper being exhausted, appears at the end of the stack. Black Theks will appear as small pieces of fly-ash are emitted. Unfortunately there isn't too much information available since only two units are presently in use. As soon as the three additional incinerators are placed in the field, more information of this type should become available.  4. Using the air-fed incinerator located in the headquarters area, two engineers were able to destroy 2,278 pounds of paper in approximately six hours. One man was able to destroy approximately 2,000 pounds of paper in an eight hour day. This paper was packed in one cubic foot boxes. Most of these boxes were opened and the contents were thrown into the burning chamber. The fibreboard boxes were destroyed at the end of the day. Burning at these rates will keep the operators relatively busy, but not overburdened.	Rome  1. Headquarters is pleased to learn that incinerators similar to the type developed by MURIOF.  2. should be made aware that when the program was initiated for the development of an air-fed incinerator the basic use of the incinerator was to be emergency destruction. After the first unit was installed at the used for the routine destruction of its classified waste files.  3. Explaining the amount of effluent emitted is rather difficult. At no time does the effluent emission ever exceed a number 2 on the Ringlesma Suoke Chart. During operation, with the exception of the time when feeding is taking place, the emission is closer to \( \frac{1}{2} \) on the Ringlesma Chart. During burning a slight gray hase, from the clay in the paper being exhausted, appears at the end of the stack. Elack flecks will appear as small pieces of fly-seck are emitted. Unfortunately there isn't too mach information available since only two units are presently in use. As soon as the three additional incinerators are placed in the field, more information of this type should become available.  4. Using the air-fed incinerator located in the headquarters area, two engineers were able to destroy 2,276 pounds of paper in an eight hour day. This paper was packed in one cubic foot boxes. Most of these boxes were opened and the centents were thrown into the burning chamber. The fibreboard boxes were destroyed at the end of the day. Euraing at these rates will keep the operators relatively busy, but not overburdened.  5. The incinerator presently located at with two motor-blower cochinations (elsetrical motor-blower and gasoline engine-blower). The elsetrical motor and blower unit is esquipped with two motor-blower cochinations (elsetrical motor-blower and gasoline engine-blower) are consisting of one final and with an electrical motor and encenting the other. A new program has recently been initiated to build a power-blower are consisting of one fina along with an electrical motor and gasoline engine-blower are consisting of one fan along	Inches Bone   Repeated to learn that   Repeated the control of the days and the same aware that when the program was initiated for the development of an air-fed incinerator the basic use of the incinerator was to be essenges destruction. After the first unit was installed at   decided this incinerator would be seed for the routine destruction of its classified waste files.  3. Explaining the amount of offluent emitted is rather difficult. At no time does the effluent emission ever emessed a masher 2 on the Ringlesam Smale Chart. During operation, with the exception of the time when feeding is taking place, the emission is closer to 2 on the Ringlesam Chart. During burning a slight gray hase, from the clay in the paper being exhausted, appears at the end of the stack. Black fleshs will appear as small pieces of fly-sah are emitted. Unfortunately there isn't too much information available since only two units are presently in use. As soon as the three additional incinerators are placed in the field, more information of this type should become available.  4. Using the air-fed incinerator located in the headquarters area, two engineers were able to destroy 2,276 pounds of paper in approximately six hours. One sam was able to destroy speculately 2,000 pounds of paper in an eight hour day. This paper was peaked in one cubic foot boxes. Most of these boxes were opened and the contents were thrown into the burning chamber. The filterhoosed boxes were destroyed at the end of the day. Burning at these rates will keep the operators relatively busy, but not overburdened.  5. The incinerator presently located at the end provide the necessary survent. Roverer, in this case, runs off the available stry current. Should the city current be cut off for some reason, an essengency generator, and provide the necessary survent. Roverer, should the esserymy generator, for some reason, fall, a 9,2 Br genoline engine-blower unit is sitting adjacent to the control of the survence of power to another by use of a clutch and belt arrangeme	· ·		MARKED FOR INDEXING		
I. Headquarters is pleased to learn that  In the similar to the type developed by KURIOT.  2. should be used aware that when the program was initiated for the development of an air-fed incinerator the basic use of the incinerator was to be emergency destruction. After the first unit was installed at decided this incinerator would be used for the routine destruction of its classified waste files.  3. Explaining the amount of effluent emitted is rather difficult. At no time does the effluent emission ever exceed a number 2 on the Ringleman Smoke Chart. During operation, with the exception of the time when feeding is taking place, the emission is closer to \( \frac{1}{2} \) on the Ringleman Chart. During bluming a slight gray hase, from the clay in the paper being exhausted, appears at the end of the stack. Black flecks will appear as small pieces of fly-ash are emitted. Unfortunately there isn't too much information available since only two units are presently in use. As soon as the three additional incinerators are placed in the field, more information of this type should become available.  4. Using the air-fed incinerator located in the headquarters area, two engineers were able to destroy 2,276 pounds of paper in approximately six hours. One man was able to destroy approximately 2,000 nounds of	1. Readquarters is pleased to learn that  incinerators similar to the type developed by MURIOT.  2. should be made aware that when the program was initiated for the development of an air-fed incinerator the basic use of the incinerator was to be emergency destruction. After the first unit was installed at decided this incinerator would be used for the routine destruction of its classified waste files.  3. Explaining the amount of effluent emitted is rather difficult. At no time does the effluent emission ever exceed a number 2 on the Ringleman Smoke Chart. During operation, with the exception of the time when feeding is taking place, the emission is closer to ½ on the Ringleman Chart. During burning a slight gray hase, from the clay in the paper being exhausted, appears at the end of the stack. Black flecks will appear as small pieces of fly-ash are emitted. Unfortunately there isn't too much information available since only two units are presently in use. As soon as the three additional incinerators are placed in the field, more information of this type should become available.  4. Using the air-fed insinerator located in the headquarters area, two engineers were able to destroy 2,278 pounds of paper in approximately six hours. One man was able to destroy approximately 2,000 pounds of paper in an eight hour day. This paper was packed in one cubic foot boxes. Most of these boxes were opened and the centents were thrown into the burning chamber. The fibreboard boxes were destroyed at the end of the day. Burning at these rates will keep the operators relatively busy, but not overburdened.	1. Readquarters is pleased to learn that incinerators similar to the type developed by NURIOT.  2. should be useds source that when the program was initiated for the development of an air-fed incinerator the basic use of the incinerator was to be emergency destruction. After the first unit was installed at decided this incinerator would be used for the routine destruction of its classified waste files.  3. Explaining the amount of effluent emitted is rather difficult. At no time does the effluent emission ever enseed a number 2 on the Ringlesan Saobe Chart. During operation, with the exception of the time when feeding is taking place, the emission is closer to ½ on the Ringlesan Chart. During burning a slight gray hase, from the clay in the paper being exhausted, appears at the end of the stack. Black flocks will appear as small pieces of fly-sch are emitted. Unfortunately there inn't too much information available since only two units are presently in use. As soon as the three additional incinerators are placed in the field, more information available since only two units are presently in use. As soon as the three additional incinerators are placed in the field, more information of this type should become available.  4. Using the air-fed incinerator located in the headquarters area, two engineers were able to destroy 2,276 pounds of paper in approximately six hours. One sam was able to destroy approximately 2,000 pounds of paper in an eight hour day. This paper was packed in one cubic foot boxes. Most of these boxes were opened and the contents were thrown into the burning chamber. The fibreboard boxes were destroyed at the end of the day. Euraing at these rates will keep the operators relatively busy, but not overburdened.  5. The incinerator presently located at the six contents were thrown into the air inlet dust provided. The motor, in this case, runs off the available sity current. Should the city current be cut off for some reason, an energency generator located elsewhere in the building will come on and	1. Headquarters is pleased to learn that  incinerators similar to the type developed by KURIOT.  2.					
1. Readquarters is pleased to learn that incinerators similar to the type developed by RIRIOT.  2. should be made sware that when the program was initiated for the development of an air-fed incinerator the basic use of the incinerator was to be emergency destruction. After the first unit was installed at decided this incinerator would be used for the routine destruction of its classified waste files.  3. Explaining the amount of effluent emitted is rather difficult. At no time does the effluent emission ever exceed a number 2 on the Ringleman Smoke Chart. During operation, with the exception of the time when feeding is taking place, the emission is closer to 2 on the Ringleman Chart. During burning a slight gray hase, from the clay in the paper being exhausted, appears at the end of the stack. Black flecks will appear as small pieces of fly-ash are emitted. Unfortunately there isn't too much information available since only two units are presently in use. As soon as the three additional incinerators are placed in the field, more information of this type should become available.  4. Using the air-fed incinerator located in the headquarters area, two engineers were able to destroy 2,276 pounds of paper in approximately six hours. One man was able to destroy approximately 2.000 nounds of	1. Headquarters is pleased to learn that incinerators similar to the type developed by RURIOT.  2. should be unde aware that when the program was initiated for the development of an air-fed incinerator the basic use of the incinerator was to be emergency destruction. After the first unit was installed at decided this incinerator would be used for the routine destruction of its classified waste files.  3. Explaining the amount of effluent emitted is rather difficult. At no time does the effluent emission ever exceed a number 2 on the Ringleman Snoke Chart. During operation, with the emeption of the time when feeding is taking place, the emission is closer to 2 on the Ringleman Chart. During burning a slight gray hase, from the clay in the paper being exhausted, appears at the end of the stack. Black flecks will appear as small pieces of fly-ash are emitted. Unfortunately there isn't too much information available since only two units are presently in use. As soon as the three additional incinerators are placed in the field, more information of this type should become available.  4. Using the air-fed incinerator located in the headquarters area, two engineers were able to destroy 2,276 pounds of paper in approximately six hours. One man was able to destroy approximately 2,000 pounds of paper in an eight hour day. This paper was packed in one cubic foot boxes. Most of these boxes were opened and the contents were thrown into the burning chamber. The fibreboard boxes were destroyed at the end of the day. Burning at these rates will keep the operators relatively busy, but not overburdened.	1. Headquarters is pleased to learn that incinerators similar to the type developed by HURIOT.  2. should be used source that when the program was initiated for the development of an air-fed incinerator the basic use of the incinerator was to be emergency destruction. After the first unit was installed at development of an air-fed incinerator the basic use of the incinerator would be used for the routine destruction of its classified wasts files.  3. Explaining the amount of effluent emitted is rather difficult. At no time does the effluent emission ever emesed a number 2 on the Ringlaman Smoke Chart. During operation, with the exception of the time when feeding is taking place, he emission is closer to ½ on the Ringlaman Chart. During burning a slight gray hase, from the clay in the paper being enhanced, appears at the end of the etack. Black fleeks will appear as small pieces of fly-ash are emitted. Unfortunately there in 't toe much information available since only two units are presently in use. As soon as the three additional incinerators are placed in the field, more information of this type should become available.  4. Using the air-fed incinerator located in the headquarters area, two engineers were able to destroy 2,270 pounds of paper in approximately six hours. One man was able to destroy approximately 2,000 pounds of paper in an eight hour day. This paper was packed in one cube foot boxes. Most of these boxes were opened and the contents were throun into the burning chamber. The fibreboard boxes were destroyed at the end of the day. Burning at these rates will keep the operators relatively busy, but not overburdened.  5. The incinerator presently located at the end of the day are the content of the motor-blower and gasoline engine-blower). The electrical motor and blower unit is connected to the air inlet dust provided. The motor, in this case, runs off the available city current. Should the city current be cut off for some reason, an energency generator, boxed of the day and both of the analysis of	1. Readquarters is pleased to learn that  incinerators similar to the type developed by KURIOT.  2. should be unde aware that when the program was initiated for the development of an air-fed incinerator the basic use of the incinerator was to be emergency destruction. After the first unit was installed at be used for the routine destruction of its classified waste files.  3. Explaining the amount of effluent emitted is rather difficult. At no time does the effluent emission ever exceed a number 2 on the Ringleson Boabe Chart. During operation, with the exception of the time when feeding is taking place, the emission is closer to 2 on the Ringleson Chart. During burning a slight gray hase, from the elay in the paper being embassied, appears at the end of the stack. Black fleeks will appear as small pieces of fly-sch are entited. Unfortunately there isn't too useh information available since only twe units are presently in use. As soon as the three additional incinerators are placed in the field, sore information of this type should become available.  4. Using the air-fed incinerator located in the headquarters area, two engineers were able to destroy 2,276 pounds of paper in approximately six hours. One sam was able to destroy approximately 2,000 pennes of paper in an eight hour day. This paper was packed in one cubic foot boxes. Most of these boxes wave opened and the contents were thrown into the burning chamber. The fibreboard boxes were destroyed at the end of the day. Burning at these rates will keep the operators relatively busy, but not overburdened.  5. The incinerator presently located at with two motor-blower conductions to the serious of a clutch and belt arrangement. The first design of this					
boxes. Most of these boxes were spened and the contents were thrown into the burning chamber. The fibreboard boxes were destroyed at the end of the day. Burning at these rates will keep the operators relatively busy, but not overburdened.	with two motor-blower combinations (electrical motor-blower and gasoline engine-blower). The electrical motor and blower unit is connected to the air inlet duct provided. The motor, in this case, runs off the available city current. Should the city current be cut off for some reason, an emergency generator located elsewhere in the building will come on and provide the necessary current. However, should the emergency generator, for some reason, fail, a 9.2 HP gasoline engine-blower unit is sitting adjacent to the elsetrical motor-blower and can be utilized by disconnecting one and connecting the other. A new program has recently been intitled.	go from one source of power to another by use of a clutch and belt	go from one source of power to another by use of a clutch and belt arrangement. The first design of this type is now being built.  6. Enclosed in a separate envelope is a complete new set of engineering drawings and a tentative set of manufacturing specifications for OOSG32  DOS 15 BEV CAYS 2 JULY 80 BY GETHYT OOSG 32  ORIG CLASS 5 BEAU 2 JULY 80 BY GETHYT ABOUT ABOUT RE 18-12  JUST 22 KEAT NEV 20/0 ADDRESS 18-12  CASSECATION	incinerators simil  2.  for the development cinerator was to be installed at be used for the round of the rou	ar to the type developed by thould be unde aware that what of an air-fed incinerator is emergency destruction. As decretion destruction of its claiming the amount of effluent energy effluent emission ever emart. During operation, with is taking place, the emission to taking place, the emission to appears at the end of the information available sin as soon as the three additions.	nurior.  on the program was initiate the basic use of the in- fter the first unit was  ided this incinerator would  assified waste files.  mitted is rather difficult.  beed a number 2 on the  in the exception of the  on is closer to ½ on the  or hase, from the clay in the  the stack. Black fleeks  litted. Unfortunately  her only two units are  local incinerators are place.	d. 2	
with two motor-blower combinations (electrical motor-blower and gasoline engine-blower). The electrical motor and blower unit is connected to the air inlet dust provided. The motor, in this case, runs off the available city current. Should the city current be cut off for some reason, an emergency generator located elsewhere in the building will come on and provide the necessary current. However, should the emergency generator, for some reason, fail, a 9.2 HP gasoline engine-blower unit is sitting adjacent to the elsetrical motor-blower and can be utilized by disconnecting one and connecting the other. A new program has recently been initiated to build a power-blower set consisting of one fan along with an electrical motor and gasoline engine. Using this combination set, an operator may go from one source of power to another by use of a clutch and belt arrangement. The first design of this type is now being built.  6. Enclosed in a separate envelope is a complete new set of engineering drawings and a tentative set of manufacturing specifications for \$\inc \frac{15}{200} = \frac{25}{200} =	6. Enclosed in a separate envelope is a complete new set of engineering drawings and a tentative set of manufacturing specifications for  008632  Dec 15 REV CATE 2 JULY 80 EY 657447  DEC 15 REV CATE 2 JULY 80 EY 657447		USE PREVIOUS EDITION. REPLACES FORMS 51-28, 51-28A AND 51-29  SECRET  **CONTINUED**  1	two engineers were six hours. One may paper in an eight i boxes. Most of the the burning chamber of the day. Burning busy, but not over 5. The ineit with two motor-blowengine-blower). The air inlet duet available city currant emergency generated provide the need for some reason, is cent to the electric one and connecting to build a power-blue to build a power-blue to and gasoline go from one source arrangement. The information of the source arrangement of the source arrangement. The information of the source arrangement of the source arrangement of the source arrangement. The information of the source arrangement of the source arrangement.	able to destroy 2,276 pound n was able to destroy approximated and the control of	is of paper in approximately clustely 2,000 pounds of saked in one cubic foot is contents were thrown into the contents were thrown into the destroyed at the end the operators relatively is equipped in a content of the cut of the cut of the cut off for some rease building will come on hould the emergency generates belower unit is sitting ad utilized by disconnecting as recently been initiated fan along with an electrical tion set, an operator may of a clutch and belt now being built.	od 2	

C	ONTINUATION OF	CLASSIFICATION	DISPA	TCH SYMBOL AND NO.	p.	
	DISPATCH	SECRET			]	25X1
				*		
· .	this mater desirement	or. It would further be a	ت قدم معالم			25X1
*	would keep headquart	ers informed of any sugges	stions l	e may have.	As	
	he starts to fabrica	te his incinerator we woul hanges he saw fit to make	ld like	to know of h	is	25X1
	program prom more co	mondes he son the co made	OH HED	WILLU.	* . 	
	-					
	Attachment: One Package		•			
		e de la companya de La companya de la co	•		•	
	25 August 1960					ľ
	Distribution:	•				2574
	3 =w/	attachment		•		25X1
	1 - TSD/SRS wo/a	ttach				
	2 - WE/6 wo/att	wo/attach				. ]
	1 - EB Chrono wo 1 - EB-178B-1 wo/	/attach				
		a c cach				or management and
	DD/P/TSD/EB/mt					
						.
		•				
	:			i	* *	
		·				
				*		
				•		l
			9	•		
				•		
						1
						]
		•				
				,		
	· ·	:				
			•		. *	
			:	•		
	. *					
		•				.
		CLASSIFICATION	T	L-T-11-	I BACE NO	
DRM 0-57 <b>53a</b>	USE PREVIOUS EDITION. REPLACES FORMS 51-28, 51-28A AND 51-29			CONTINUED	PAGE NO.	
(40)	WHICH ARE OBSOLETE.	SECRET	15		2	1